

Flash Unit		Hi-Sync	Power Control	Power Display on Transmitter	Triggering
Quadra ^① 1st series	Action (A) Head				
	Pro (S) Head				
Quadra RX ^① 2nd series	HS Head				
	RQ Ringflash Pro				
Quadra Hybrid ^① 3rd series	RQ Ringflash Eco				
Ranger RX (inc Speed and Speed AS) with Transceiver RX	A Head				
	S Head				
D-Lite IT	2				
	4				
D-Lite RX	ONE				
	2				
	4				
BXRi	250/500				
BRX	250/500				
ELC Pro HD	500/1000				
Style RX with Transceiver RX	300				
	600				
	1200				
Digital RX 1200 with Transceiver RX	Action Zoom Head				
	Pro Zoom Head				
	Pro HD Zoom Head				
	Ringflash 3000				
Digital RX2400 with Transceiver RX	Action Zoom Head				
	Pro Zoom Head				
	Pro HD Zoom Head				
	Ringflash 3000				
Universal Receiver					
WiFi Modul used as a receiver					
Transceiver RX					

① We recommend output A (slower flash duration)

② For individual unit power control ensure unit is in a group on it's own

Recommended for Hi-Sync

Not optimized for Hi-Sync.
Shutters speeds higher than 1/600s might produce unexpected results depending on flash units, power levels and camera sensor size.

Feature not available

Feature available