

 elinchrom®

THREE



Never settle  
for ordinary.



Kontichsesteenweg 41 - 2630 Aartselaar  
info@servix.be [www.servix.be](http://www.servix.be)

# Elinchrom THREE

Always be ready when inspiration strikes with the supremely compact and lightweight Elinchrom THREE. With only 1,65kg, the THREE merges 261Ws of capacity with features including Li-ion battery, USB-C active charging, TTL, HSS and a streamlined touch interface into a low profile housing.

## Keep a low profile

Add the versatility of an off-camera flash with the light shaping capabilities to any kit while maintaining a minimal footprint with the Elinchrom THREE. Similar in size and weight to a 70-200 zoom lens, the THREE is ready to travel with you anywhere and everywhere.



## Your choice of light modifiers

Engineered to use the newly developed Elinchrom OCF modifier mount, the Elinchrom THREE is compatible with most Profoto© OCF light shapers, expanding your selection of available light shaping tools. The included EL-Profoto adapter enables quick mounting to light modifiers using the traditional Elinchrom bayonet.

## Navigate swiftly

With a touchscreen interface and a newly designed menu structure, experience a streamlined access to the THREE's settings to ensure you never miss a chance to capture the moment.

## Brave the elements

The Elinchrom THREE utilizes a sealed Li-ion battery for maximum portability and enhanced protection from the elements while on location. You are not tied to spare batteries or chargers with the ability to charge from any USB-C source.

## Never loose momentum

Capable of producing 525 full-power flashes on a single charge, the THREE is ready for longer shoots. Additionally the THREE can be connected to a power source and continue shooting while charging regardless of the battery's power level, keeping your workflow uninterrupted.



# Elinchrom **THREE** SPECIFICATIONS

UNIT	<b>Energy</b> (Ws/J)	261
	<b>F-Stop</b> (1m, 100 ISO, HP Reflector 26 cm (10.2"), max power)	64.3
	<b>F-Stop</b> (1m, 100 ISO, OCF Diffusion Dome, max power)	22.0
	<b>Power range</b> (F-Stop)	6
	<b>Power range</b> (Ws/J)	7 – 261
	<b>Power range display</b>	0.1 – 5.3 (Elinchrom scale) / 4.8 – 10 (10 scale)
	<b>Power increments in Manual / TTL mode</b>	0.1 F-Stop / 0.3 F-Stop
	<b>Flash duration t0.1 min/max power</b> (Standard mode)	1/1550s – 1/255s
	<b>Flash duration t0.1 min/max power</b> (Action mode)	1/8500s – 1/440s
	<b>Recycling time min/max power</b>	0.08s / 1.2s
	<b>Flash mode</b>	Manual / TTL / HSS (with Transmitter Pro)
	<b>Action mode</b>	Faster flash duration over the power range
	<b>Flash colour temperature at max power</b>	5900 K (Action) / 5600 K (HSS)
	<b>Flash colour stability over the power range</b> (all modes)	±150 K
	<b>Power stability</b>	±0.5%
<b>Auto power dumping</b>	Adjusts power settings automatically in real time	
<b>Fan cooled</b>	Smart proactive cooling	
<b>Input</b>	USB-C	
BATTERY	<b>Battery</b>	Li-Ion - Built-in - 41.04Wh
	<b>Battery capacity min/max power</b> (LED lamp OFF)	11250 / 525
	<b>Battery capacity min/max power</b> (LED lamp ON 100%)	9000 / 420
	<b>Battery charge status</b>	On the display if ON and side logo if OFF
	<b>Charging time</b> (with 65W USB-C Wall Charger)	60 m (80%) – 100 m (100%) / Fast charge (unit is ON) 80 m (80%) – 135 m (100%) / Slow charge (unit is OFF)
	<b>Charging time</b> (with 18W 20000 mAh Power Bank)	80 m (80%) – 135 m (100%) / Fast charge (unit is ON) 105 m (80%) – 180 m (100%) / Slow charge (unit is OFF)
LED	<b>LED modeling lamp modes</b>	ON/OFF, free, proportional, VFC
	<b>LED modeling lamp power</b>	20W / equivalent to 120W / 3000 lm / CRI 95
	<b>LED modeling lamp color temperature</b>	Presets from 2700 K to 6500 K
	<b>LED run time</b> (LED only, min/max power)	10 hours / 90 minutes
RADIO	<b>Skyport</b> (built-in)	20 frequency channels, 4 Groups
	<b>Skyport distance range</b> (Transmitter Pro, manual mode)	Indoor: up to 60 m / Outdoor: up to 200 m
	<b>Bluetooth</b> (built-in)	Version 4.2 / Compatible Studio Software Win, Mac, iOS, Android
SIZE	<b>Umbrella fitting</b> (on tilt head)	7 – 8 mm
	<b>Dimensions</b> with Diffusion Dome and tilt head	25.3 x 16.5 x 10.5 cm 10 x 6.5 x 4.1 inches
	<b>Dimensions</b> without Diffusion Dome and tilt head	24.5 x 10 x 10 cm 9.7 x 3.9 x 3.9 inches
	<b>Weight</b> (with/without tilt head)	1.65 kg – 3.6 lbs / 1.45 kg – 3.2 lbs

# Elinchrom **THREE** KITS

## Off camera flash kit - EL20941



- 1x Elinchrom THREE
- 1x Elinchrom Profoto adapter
- 1x Elinchrom OCF Diffusion dome
- 1x Elinchrom 65W USB-C charger
- 1x Elinchrom USB-C cable 1,8m
- 1x Elinchrom case
- 2 Year warranty

## Off camera dual flash kit - EL20942



- 2x Elinchrom THREE
- 2x Elinchrom Profoto adapter
- 2x Elinchrom OCF Diffusion dome
- 2x Elinchrom 65W USB-C charger
- 2x Elinchrom USB-C cable 1,8m
- 1x Elinchrom backpack
- 2 Year warranty

# Elinchrom **THREE** ACCESSORIES



EL25112  
OCF Gel dome kit



EL25110  
OCF diffusion dome



EL26246  
Elinchrom OCF Adapter



EL26246  
OCF Wide reflector



EL26002  
OCF Barndoors



EL33252  
Elinchrom ONE Backpack